


Aluminum I-Beam

6061 - T6 Aluminum Association I-Beam - Canadian




■ Stocked in 20 foot lengths

Width (A)	Flange (B)	Web (C)	Thickness (D)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number Canada	Length
3	2 1/2	.130	.200	.250	1.637	32.740	553451	20 ft
3	2 1/2	.150	.260	.250	2.030	50.750	729939*	25 ft
3	2 1/2	.188	.250	.375	2.164	43.280	553427	20 ft
4	3	.150	.230	.250	2.311	57.775	754277*	25 ft
4	3	.170	.290	.250	2.793	69.825	637938*	25 ft
4	3	.188	.250	.250	2.680	53.600	553435	20 ft
5	3 1/2	.190	.320	.300	3.700	92.500	541917*	25 ft
6	4	.190	.280	.300	4.030	100.750	623476*	25 ft
6	4	.210	.350	.300	4.692	93.840	553443	20 ft
6	4	.281	.375	.437	5.455	109.100	553469	20 ft
6	4	.281	.375	.437	5.455	136.375	635512*	25 ft
6	6	.312	.375	.626	7.769	155.380	550568	20 ft
6	6	.375	.500	.625	9.655	193.100	550576	20 ft
7	4 1/2	.230	.380	.300	5.800	145.000	628484*	25 ft
8	5	.230	.350	.300	6.181	154.525	632831*	25 ft
8	5	.250	.410	.300	7.023	175.580	595217*	25 ft
10	6	.250	.410	.400	8.646	216.150	541030*	25 ft
12	7	.290	.470	.400	11.672	291.800	695538*	25 ft
12	7	.310	.620	.400	14.292	357.300	596289*	25 ft

* Stocked in 25 foot lengths
Dimensions are in inches. All weights are approximate.

6061 - T6 Wide Flange I-Beam - Canadian




■ Stocked in 20 foot lengths

Width (A)	Flange (B)	Web (C)	Thickness (D)	Radius (R)	Lbs/Ft	Lbs/Length	Part Number Canada	Length	
4	4	.250	.312	.437	4.121	82.420	550550	20 ft	Square Toes
6	4	.230	.279	.250	4.161	104.030	754497*	25 ft	Square Toes
6	6	.240	.269	.250	5.401	135.030	566179*	25 ft	Square Toes
8	8	.288	.433	.400	10.725	268.125	602454*	25 ft	Square Toes

* Stocked in 25 foot lengths
Dimensions are in inches. All weights are approximate.

Aluminum I-Beam

6061 - T6 American Standard I-Beam



■ Stocked in 20 and 25 foot lengths

Width (A)	Flange (B)	Web (C)	Thickness (D)	Radius (R ₁)	Radius (R ₂)	Lbs/Ft	Lbs/Length	Part Number Canada
3	2.330	.170	.170	.270	.100	1.963	49.075	610847*
3	2.509	.349	.170	.270	.100	2.595	64.875	740595*
4	2.660	.190	.190	.290	.110	2.660	66.100	541373*
4	2.796	.326	.190	.290	.110	3.283	82.075	754285*
4	4.000	.313	.290	.313	.145	4.758	118.950**	684383*
5	3.000	.210	.210	.310	.130	3.430	68.680	550592
5	5.000	.313	.330	.313	.165	6.494	162.350	597065*
6	3.330	.230	.230	.330	.140	4.302	107.550	587793*
8	4.000	.270	.260	.370	.160	6.348	127.000	550615
8	4.262	.532	.270	.370	.180	8.813	220.330	754269*
10	4.660	.310	.310	.410	.190	8.764	219.100	540911*

* Stocked in 25 foot lengths

** H-Beam

Dimensions are in inches. All weights are approximate.