


Brass Sheet & Plate

Non-Leaded Brass Sheet & Plate, Half Hard Temper



- UNS Designation Number: UNS C26000
- Nominal Chemicals: Copper 70%, Zinc 30%
- Average Physical Properties: Tensile 62,000 psi, Hardness B68, Machinability = 30
- Specifications: ASTM B 36, Temper H02 (1/2 Hard)

Gauge	Thickness	Size of Sheet	Lbs/Sq Ft	Lbs/Sheet	Part Number
26	.016	24 x 96	.705	11.28	127315
24	.020	36 x 96	.881	21.14	103036
22	.025	36 x 96	1.10	26.45	157784
20	.032	36 x 96	1.41	33.84	157865
18	.040	36 x 96	1.76	42.29	157881
16	.050	36 x 96	2.20	52.87	157904
14	.063	36 x 96	2.77	66.55	157920
11	.090	36 x 96	3.97	95.16	157946
1/8	.125	36 x 96	5.51	132.2	157962
3/16	.1875	36 x 96	8.26	198.2	157988
1/4	.250	36 x 96	11.02	264.5	158007
5/16	.3125	36 x 96	13.77	330.5	420153
3/8	.375	36 x 96	16.52	396.5	409822
1/2	.500	36 x 96	22.18	542.5	419186
3/4	.750	36 x 96	33.05	793.2	158031
1	1.00	36 x 96	44.06	1057	432095

Non-Leaded Brass Sheet & Coil, Soft Temper

- UNS Designation Number: UNS C26000
- Nominal Chemicals: Copper 70%, Zinc 30%
- Average Physical Properties: Tensile 45,000, Hardness F70
- Specifications: ASTM B 36, Annealed

Gauge	Thickness	Size of Sheet	Lbs/Sq Ft	Part Number
36	.005	12 x COIL	.220	157564
30	.010	12 x COIL	.441	157572
26	.016	12 x COIL	.705	157598
22	.025	12 x COIL	1.10	157629
18	.040	36 x 96	1.76	127404
16	.050	36 x 96	2.20	267709
14	.063	36 x 96	2.77	246850

Dimensions are in inches. All weights are approximate.