

## "Annealed" Welded and Seamless Tubing



- "Annealed" tubing is used when the specifications referenced below are required. This tubing is primarily used for instrumentation, heat exchangers and in some ornamental applications.
- Welded "annealed" tubing is available per ASTM A 249, ASME SA-249 and ASTM A 269 and is stocked to 4" OD and available up to 8" OD.
- Seamless "annealed" tubing is available per ASTM A 213, ASME SA -213 and ASTM A 269 and is stocked to 2" OD and available up to 6" OD.
- Alloys stocked include Types 304, 304L, 316, 316L and 317L. Other corrosion resistant alloys are available.
- Available in 20 foot random lengths.

Outside Diameter	Weight per Foot								
	Wall Thickness:		Listed in Inches						
	.020	.028	.035	.049	.065	.083	.095	.109	.120
1/16	.01								
1/8	.02	.03	.03	.04					
3/16	.04	.05	.06	.07	.09				
1/4	.05	.07	.08	.11	.13	.15			
5/16	.06	.09	.11	.14	.18	.21			
3/8	.08	.11	.13	.17	.22	.26			
7/16	.09	.13	.15	.21	.26	.32			
1/2	.10	.14	.18	.24	.31	.38	.42	.47	.50
9/16	.12	.16	.20	.28	.35	.44			
5/8	.13	.18	.23	.31	.40	.49	.55	.61	.66
3/4	.16	.22	.27	.38	.49	.61	.68	.76	.83
7/8	.19	.26	.32	.44	.58	.72	.81	.91	.99
1	.21	.30	.37	.51	.66	.83	.94	1.1	1.2
1 1/4			.46	.64	.84	1.1	1.2	1.4	1.5
1 5/16			.49	.68	.89	1.1	1.3	1.4	1.6
1 1/2			.56	.78	1.0	1.3	1.5	1.7	1.8
1 5/8			.61	.84	1.1	1.4	1.6	1.9	2.0
1 3/4			.66	.91	1.2	1.5	1.7	2.0	2.1
2			.75	1.0	1.4	1.7	2.0	2.3	2.5
2 1/4				1.2	1.6	2.0	2.2	2.6	2.8
2 3/8				1.2	1.6	2.1	2.4	2.7	3.0
2 1/2				1.3	1.7	2.2	2.5	2.8	3.0
2 7/8					2.0	2.5	2.9	3.3	3.6
3					2.1	2.6	3.0	3.4	3.8
3 1/2					2.4	3.1	3.5	4.0	4.4
4					2.8	3.6	4.1	4.6	5.1
4 1/2					3.2	4.0	4.6	5.2	5.7
5					3.5	4.5	5.1	5.8	6.4
6					4.2	5.4	6.1	7.0	7.7
8					5.6	7.2	8.2	9.4	10.3

All weights are in pounds per foot, based on a metal density of .29 lb/in<sup>3</sup>  
 Dimensions are in inches.  
 Alloys: pg. 55 Tolerances: pg. 57 Specifications: pg. 52, 53